

Test Verification of Conformity

In the basis of the tests undertaken, the sample(s) of the below product have been found to comply with the requirements of the referenced specifications at the time the tests were carried out.

Applicant Name & Address:	Enstall US, Inc. 41 West Putnam Avenue, Suite 303 Greenwich, CT 06830-5300 USA
Product Description: Ratings & Principle Characteristics:	Symmetrical Mount for Low and Steep Slope Roof Applications <u>Fire Class Resistance Rating:</u> Class A Fire Rated for Low and Steep Slope applications when using Type 1, 2, 3, 13, 19, 25, 29, 30 and 38 listed photovoltaic modules. Class A Fire Rated for Steep Slope applications when using Type 4 and 5 listed photovoltaic modules, low edge guarding required. Class B Fire Rated for Steep Slope applications when using Type 4 and 5 listed photovoltaic modules, no perimeter guarding is required. This system was evaluated with a 5" gap between the bottom of the module and the roof's surface. Per UL 2703 this product can be installed with any gap stated in the manufacturer's installation instructions. A wind deflector is optional. This rating is applicable with any 3rd party roof attachments with similar construction and materials.
Models:	Ecofasten Clickfit
Brand Name: Relevant Standards:	Ecofasten UL 2703 (2023) (Section 15.2 and 15.3) Standard for Safety Mounting Systems, Mounting Devices, Clamping/Retention Devices with Flat-Plate Photovoltaic Modules and Panels, Referencing UL2703 2023 (Section 31.2) Standard for Safety for Flat-Plate Photovoltaic Modules and Panels.
Verification Issuing Office:	Intertek Testing Services NA, Inc. 8431 Murphy Drive Middleton, WI 53562
Date of Tests:	03/06/2019 – 06/19/2020
Test Report Number(s):	104337595MID-001 (Type 2, performed by Intertek) R1-ECF190206_Rev2 (Type 1, performed by SolarPTL) 105310735MID-001, 105499394MID-008 PEV, 105499394MID-008, 106404079MID-001
Revision History:	1/8/24 added type 4 and 5, 06/18/25 added type 30, 12/11/25 added type 3, 13, 19 and 25 panels.

This verification is part of the full test report(s) and should be read in conjunction with them. This report does not automatically imply product certification.

Completed by: Seth Newman	Reviewed by: Chad Naggs
Title: Technician, Fire Resistance	Title: Technical Team Lead – Fire Resistance
Signature: 	Signature: 
Date: 12/11/25	Date: 12/11/25

This Verification is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Verification. Only the Client is authorized to permit copying or distribution of this Verification. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test/inspection results referenced in this Verification are relevant only to the sample tested/inspected. This Verification by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.